

The Rifleman Charger allows the user to maintain up to 80% charge on an Thales Rifleman Radio in a vest or personal equipment mounted package. The charger

may be used as part of the Soldier Wearable Integrated Power Equipment System (SWIPES™) system or separately powered using SWIPES™ compatible power cable.

Male Connector



A - Black B - Brown C - Red

Female Connector



A - Black B - Brown C - Red

PRODUCT SPECIFICATION

RIFLEMAN AN/PRC 154 CHARGER



GENERAL SPECIFICATIONS

Compatible with the following batteries and Power Source:

BA-8180/U

BA-8140/U

BA-5590/U

BA-5390/U

BA-2590/U

BB-390/U

BB-590/U

Li-145

CWB-85

CWB-150

SWIPES Power Hub

DC Input

12 VDC Nominal

Output:

1 Amp 12.6 VDC Maximum

Operational Temperature:

-20°C to +60°C (-4°F to +140°F)

Storage Temperature:

-40°C to +100°C (-40°F to +212°F)

Dimensions:

77 x 35 x 96 cm (3.0 x 1.38 x 3.75 inches)

Weight:

142 g / 0.31 lb

Environmental:

Humidity 95% Altitude 50,000 ft

Part Numbers:

EFB: 1-15150-00 UEC: 0998A01-003 NSN: 6150016123379