

The Falcon III AN/PRC 152 Charger with Auxiliary Output Cable and with Falcon Dual Input Dual Output side collector (sidePAN) allows the user to maintain up to 80%, charge on a Harris Falcon III Radio, charge a EUD and provides an output to exchange data between an EUD and Radio in a vest or personal equipment mounted package. The charger may be used as part of the SWIPES™ system or separately powered using a SWIPES™ compatible power cable. Kit comprised of Falcon III Charger and SidePAN Connection.

PRODUCT SPECIFICATION

FALCON III AN/PRC 152 CHARGER W/ AUXILIARY OUTPUT CABLE AND WITH FALCON DUAL INPUT DUAL OUTPUT SIDE CONNECTOR (SIDEPAN)

Male Connector A - Black B - Brown

B - Brown C - Red

Female Connector



A - Black B - Brown C - Red



GENERAL SPECIFICATIONS

Compatible with the following batteries & Power Source:

BA-8180/U

BA-8140/U

ZA-8140S

ZA-8150

SWIPES™ Power Hub

BA-5590/U

BA-5390/U

BA-2590/U

BB-390/U

BB-590/U

Li-145

CWB-85

CWB-150

DC Input:

12 VDC Nominal

DC Output Charge:

12.6 VDC Maximum

DC Output Side Cable:

5VDC Nominal 1 A Maximum

Operational Temperature:

-20°C to +60°C (-4°F to +140°F)

Storage Temperature:

-40°C to +100°C (-40°F to +212°F)

Dimensions (WxDxL):

7.7 x 3.5 x 9.6 cm (3.0 x 1.38 x 3.75 inches)

Weight:

133 q / 0.29 lb

Environmental:

Humidity 95% Altitude 50,000 ft

Part Numbers:

EFB: 1-15250-SH UEC: 1045A01-003 NSN: 6130016185758