



UEC Electronics  
5914 Howard Street, Hanahan, SC 29410  
843-552-8682



## Rifleman AN/PRC 154 Charger with Auxiliary Output Cable

**EFB P/N: 1-15150-XSH**

### **Charger Description**

EFB's Rifleman AN/PRC 154 Charger with Auxiliary Output Cable allows the user to maintain up to 80% charge on an Thales Rifleman Radio charge a EUD and provides an output to exchange data between ab EUD and Radio in a vest or personal equipment mounted package. The charger may be used as part of the SWIPES™ system or separately powered using the SWIPES™ Power Cable, AM/GF (EFB P/N 1-15500-00). The Auxiliary Putput Cable shall be connected to a Rifleman AN/PRC 154 Charger Sidehat device (EFB P/N 1-15159-00) ONLY.

### **Compatible with the following batteries & Power Source**

BA-8180/U, BA-8140/U, ZA-8140S, ZA-8150, IPS HUB, BA-5590/U, BA-5390/U, BA-2590/U, BB-390/U, BB-590/U

### **DC Input**

12 VDC Nominal

### **Output**

1 Amp 12.6 VDC Maximum

### **DC Ouput Side Cable**

5V DC Nominal

1 A Maximum

### **Storage Temperature**

-40°C to +100°C (-40°F to +212°F)

### **Dimensions (WxDxL)**

.077 x .035 x .096 Meters (3.03 x 2.49 x3.84 Inches) Nominal

### **Weight**

.171 kg (0.377 lb) Nominal

### **Environmental**

-Humidity 95%

-Altitude 50,000 ft