




PRODUCT SPECIFICATION

RIFLEMAN AN/PRC 154 CHARGER W/ AUXILIARY OUTPUT CABLE AND WITH RIFLEMAN DUAL INPUT DUAL OUTPUT SIDE CONNECTOR (SIDEPAN)

The Rifleman AN/PRC 154 Charger with Auxiliary Output Cable and with Dual Input Dual Output side connector (sidePAN) allows the user to maintain up to 80% charge on an Thales Rifleman Radio, charge a EUD and provides an output to exchange data between an EUD and Radio in a vest or personal equipment mounted package. The charger may be used as part of the SWIPES™ unit or separately powered using a SWIPES™ Compatible Power Cable.



GENERAL SPECIFICATIONS

Compatible with the following batteries & Power Source:

- BA-8180/U
- BA-8140/U
- ZA-8140S
- BA-5590/U
- BA-5390/U
- BA-2590/U
- BB-390/U
- BB-590/U
- Li-145
- CWB-85
- CWB-150
- SWIPES Power Hub

DC Input:
12 VDC Nominal

Output:
1 Amp 12.6 VDC Maximum

Operational Temperature:
-20°C to +60°C (-4°F to +140°F)

Storage Temperature:
-40°C to +100°C (-40°F to +212°F)

Dimensions (WxDxL):
25 x 11.5 x 31.4 cm (3.03 x 2.49 x 3.84 inches)

Weight:
227 g / 0.498 lb

Environmental:
Humidity 95%
Altitude 50,000 ft

Part Numbers:
EFB: 1-15150-SH
UEC: 0998A01-002
NSN: 6130016185990