




## PRODUCT SPECIFICATION

### RIFLEMAN AN/PRC 154 CHARGER W/ AUXILIARY OUTPUT CABLE

The Rifleman AN/PRC 154 Charger with Auxiliary Output Cable allows the user to maintain up to 80% charge on an Thales Rifleman Radio charge a EUD and provides an output to exchange data between ab EUD and Radio in a vest or personal equipment mounted package. The charger may be used as part of the Soldier Worn Integrated Power Equipment System (SWIPES™) system or separately powered using a SWIPES™ compatible power cable. The Auxiliary Output Cable shall be connected to a Rifleman AN/PRC 154 Charger device.



## GENERAL SPECIFICATIONS

### Compatible with the following:

- BA-8180/U
- BA-8140/U
- IPS HUB
- BA-5590/U
- BA-5390/U
- BA-2590/U
- BB-390/U
- BB-590/U

### DC Input

12 VDC Nominal

### DC Output:

1 Amp 12.6 VDC Maximum

### Operational Temperature:

-20°C to +60°C (-4°F to +140°F)

### Storage Temperature:

-40°C to +100°C (-40°F to +212°F)

### Dimensions:

7.7 x 3.5 x 9.6 cm (3.03 x 2.49 x 3.84 inches)

### Weight:

171 g / 0.377 lb

### Environmental:

Humidity 95%  
Altitude 50,000 ft

### Part Numbers:

EFB: 1-15150-XSH  
UEC: 0998A01-002  
NSN: 6130016185787